HOLOSUN

507 COMP

Open competition red dot · 2 MOA dot + 8/20/32 MOA circles



INCHES PER CLICK

1 CLICK = 1 MOA

DISTANCE	MOVES IMPACT
100 YD	1.05"
50 YD	0.52"
25 YD	**0.26"**
15 YD	0.16"
10 YD	0.10"
7 YD	0.07"
5 YD	0.05"

At 25 yd: ≈ 4 clicks = 1 inch

Flat-tip tool · **counter-clockwise** = impact **UP** · **clockwise** = impact **LEFT**

OPERATION

ON	Press + or −
OFF	+ and − together (stops Shake Awake)
BRIGHT	+ / − · remembers last setting
LOCK	Hold + 3 s (on / off)
RETICLE	Hold − 3 s: 8 reticle combinations
SLEEP	Shake Awake · 10 min default

BATTERY

TYPE	CR1632
INSTALL	+ side DOWN in tray
ACCESS	Side tray · T10 screw · optic stays on
LIFE	50,000 hrs on setting 6

SPECS

WEIGHT	1.7 oz
FOOTPRINT	RMR
WATER	IP67
WINDOW	1.1" × 0.87"

1 MOA = 1.047 in at 100 yd. Inches/click = MOA/click × 1.047 × yd ÷ 100. Source: Holosun HS507COMP product page & 507COMP manual. Confirm zero with live fire.