STRATEGIC DEFENSE ACADEMY

HOLOSUN

EPS CARRY

Enclosed carry red dot · 2 MOA dot (EPS-CARRY-RD-2)



INCHES PER CLICK

1 CLICK = 1.5 MOA

NOT 1 MOA — EACH CLICK IS 1.5 MOA

DISTANCE	MOVES IMPACT
100 YD	1.57"
50 YD	0.79"
25 YD	**0.39"**
15 YD	0.24"
10 YD	0.16"
7 YD	0.11"
5 YD	0.08"

At 25 yd: ≈ 2.5 clicks = 1 inch

Included tool · elevation on rear, windage on right side

OPERATION

ON	Press **+** or **−**
OFF	**+** and **−** together (stops Shake Awake)
BRIGHT	12 settings · 1–4 NV, 5–12 day · memory
LOCK	Hold **+** 3 s (on / off)
SLEEP	After 10 min still · motion wakes

BATTERY

TYPE	**CR1620** (not CR1632)
ACCESS	Side tray · optic stays on
LIFE	50,000 hrs on setting 6

SPECS

WEIGHT	1.23 oz
FOOTPRINT	K (RMSc-to-K plate incl.)
WATER	IPX8
SIGHT	Built-in rear notch

1 MOA = 1.047 in at 100 yd. Inches/click = MOA/click × 1.047 × yd ÷ 100. Source: Holosun EPS Carry product page & EPS manual. Confirm zero with live fire.