STRATEGIC DEFENSE ACADEMY

Trijicon

RMR HD

Open pistol red dot · 1 MOA dot + 55 MOA ring (RMHD1)



INCHES PER CLICK

1 CLICK = 1 MOA

DISTANCE	MOVES IMPACT
100 YD	1.05"
50 YD	0.52"
25 YD	**0.26"**
15 YD	0.16"
10 YD	0.10"
7 YD	0.07"
5 YD	0.05"

At 25 yd: ≈ 4 clicks = 1 inch

Slot · **counter-clockwise** moves impact **UP / RIGHT**

OPERATION

ON	Press **+** or **−** (starts in auto)
BRIGHT	**+** / **−** · 9 settings (1–3 NV)
AUTO	Press both < 1 s
OFF	Hold both ≥ **6 s** (dot blinks at 3 s)
TIMER	Manual reverts to auto after 16.5 hr

BATTERY

TYPE	CR2032
INSTALL	**+** side faces UP
ACCESS	Top cap · optic stays on
LIFE	3+ yrs on setting 5 of 9 (dot only)

SPECS

RETICLE	1 or 3.25 MOA dot + 55 MOA ring
WEIGHT	1.69 oz
FOOTPRINT	RMR
WATER	Waterproof 66 ft
TORQUE	15 in-lb (mount screws)

1 MOA = 1.047 in at 100 yd. Inches/click = MOA/click × 1.047 × yd ÷ 100. Source: Trijicon RMR HD product page & manual. Confirm zero with live fire.