STRATEGIC DEFENSE ACADEMY

Trijicon

# RMR TYPE 2

Open pistol red dot · 3.25 MOA adjustable LED (RM06)



## INCHES PER CLICK

## 1 CLICK = 1 MOA

| DISTANCE | MOVES IMPACT |
|---|---|
| 100 YD | 1.05" |
| 50 YD | 0.52" |
| **25 YD** | **0.26"** |
| 15 YD | 0.16" |
| 10 YD | 0.10" |
| 7 YD | 0.07" |
| 5 YD | 0.05" |

**At 25 yd: ≈ 4 clicks = 1 inch**

Slot · **counter-clockwise** moves impact **UP / RIGHT**

## OPERATION

| | |
|---|---|
| ON | Press **+** or **−** (starts in auto) |
| BRIGHT | **+** / **−** · 8 manual settings (NV) |
| AUTO | Press both < 1 s |
| OFF | Hold both ≥ 3 s |
| LOCK-OUT | Hold one button 3 s |
| TIMER | Manual reverts to auto after 16.5 hr |

## BATTERY

| | |
|---|---|
| TYPE | CR2032 |
| ACCESS | **Bottom-load: REMOVE optic** from slide |
| INSTALL | **−** side down · slide in front-to-rear |
| LIFE | 4+ yrs on setting 4 of 8 |

## SPECS

| | |
|---|---|
| DOT | 3.25 MOA (also 1, 6.5) |
| WEIGHT | 1.2 oz |
| FOOTPRINT | RMR |
| WATER | Waterproof 66 ft |
| TORQUE | 15 in-lb (mount screws) |

**1 MOA = 1.047 in at 100 yd.** Inches/click = MOA/click × 1.047 × yd ÷ 100. Source: Trijicon RMR Type 2 product page & manual. Confirm zero with live fire.