Trijicon

SRO

Open pistol red dot · 2.5 MOA adjustable LED (SRO2)



INCHES PER CLICK

1 CLICK = 1 MOA

DISTANCE	MOVES IMPACT
100 YD	1.05"
50 YD	0.52"
25 YD	**0.26"**
15 YD	0.16"
10 YD	0.10"
7 YD	0.07"
5 YD	0.05"

At 25 yd: ≈ 4 clicks = 1 inch

Coin / slot · **counter-clockwise** moves impact **UP** / **RIGHT**

OPERATION

ON	Press **+** or **−** (starts in auto)
BRIGHT	**+** / **−** · 8 manual (2 NV, 6 day)
AUTO	Press both < 1 s
OFF	Hold both ≥ 3 s
TIMER	Manual reverts to auto after 16.5 hr

BATTERY

TYPE	CR2032
INSTALL	**+** side faces the cap
ACCESS	Top-load cap · optic stays on
LIFE	3+ yrs on setting 4 of 8 (red)

SPECS

DOT	1.0 / 2.5 / 5.0 MOA
WEIGHT	1.6 oz
FOOTPRINT	RMR
WATER	Waterproof 10 ft
TORQUE	15 in-lb (mount screws)

1 MOA = 1.047 in at 100 yd. Inches/click = MOA/click × 1.047 × yd ÷ 100. Source: Trijicon SRO product page & manual. Confirm zero with live fire.